





Media basket available separately

Now is the time to grow your business by offering a greater range of products and a faster, more reliable service. **The CAMM-1 GR2 series** of large format cutting plotters from Roland DG is built to fit seamlessly with your print-then-cut workflow and deliver fast, flawless results from day one.

Visit **www.rolanddg.com.au/gr2** for further information




Great Return on Investment

Affordable and powerful, the CAMM-1 GR2 series easily raises your production and profits.



User-friendly for Immediate Production

Plug in and start working immediately thanks to Roland DG's user-friendly interface.



Integrates with Your Printer

Advanced Roland DG software gives you an easy way to work with print-only technology.



The Roland DG Legacy

Make a safe investment with Roland DG's world renowned quality and reliability.



VEHICLE GRAPHICS

VERSATILE SIGNAGE



HEAT TRANSFER APPAREL

CONTOUR CUT LABELS

WINDOW AND WALL GRAPHICS

SPECIFICATION

| Model | | GR2-640 | GR2-540 |
|----------------------------|-------------|---|---|
| Drive system | | Digital control servo motor | |
| Cutting mechanism | | Media-moving method | |
| | Width | 50 mm to 1,782 mm (1.97 in. to 70.1 in.) | 50 mm to 1,594 mm (1.97 in. to 62.7 in.) |
| Acceptable media Thickness | | 0.8 mm (31.4 mil.) or less including backing paper | |
| | Roll weight | 24 kg (52.9 lb.) | 20 kg (44.1 lb.) |
| Maximum cutting area | | 1,627 mm × 50,000 mm (64 in. × 1,968 in.) | 1,372 mm × 50,000 mm (54 in. × 1,968 in.) |
| Cutting speed | | 30 to 1,530 mm/s (1.19 to 60 in./s) | |
| Blade force | | 5 - 600 gf | |
| Mechanical resolution | | 0.006 mm/step (0.236 mil./step) | |
| Repeatability | | 0.1 mm (3.94 mil.) or less | |
| Distance Accuracy | | Error of less than ±0.1% of distance traveled or 0.254 mm (10 mil.), whichever is greater | |
| Software resolution | | 0.025 mm/step (0.98 mil./step) | |
| Connectivity | | Ethernet (automatic switching between 10BASE-T and 100BASE-TX) USB 2.0 (FULL SPEED compliant) RS-232C | |
| Replot memory | | 32 MB | |
| Power requirements | | AC 100 to 240 V ± 10%, 50/60 Hz (Consumption approx. 110 W) | |
| Dimensions / Weight | | 1,982 mm × 756 mm × 1,127 mm (78.1 in. × 30 in. × 44.4 in.) / 69 kg (153 lb.) | 1,711 mm × 651 mm × 1,111 mm (68 in. × 25.7 in. × 44 in.) / 60 kg (133 lb.) |
| Included items | | USB cable, cutting pad, safe blade, dedicated stand, tweezers, user's manual, etc. | |

Roland DG reserves the right to make changes in specifications, materials or accessories without notice. Actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland DG dealer for details. No guarantee or warranty is implied other than expressly stated. Roland DG shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Reproduction or use of copyrighted material is governed by local, national, and international laws. Customers are responsible for observing all applicable laws and are liable for any infringement. Roland DG Corporation has licensed the MMP technology from the TPL Group.



www.rolanddg.com.au

AUTHORISED DEALER:

