



# HP Latex 700 Printer

Grow with high-value jobs and sharpen your sustainability edge with HP Latex Technology



## Win the high-value jobs you are after

- Deliver vivid colors at high speed and get striking contrast using pure blacks.
- Expect reliable, sharp 4-point text with HP Latex printheads featuring 10-picoliter ink drops.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

## Beat your deadlines with smart, efficient printing

- Fast saturated color up to 334 ft<sup>2</sup>/hr outdoor, 226 ft<sup>2</sup>/hr indoor.<sup>1</sup>
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 121 lb (55 kg).

## Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs<sup>2</sup>, no required hazard warning labels, and odorless prints.<sup>3</sup>
- Zero landfill—local outer carton recycling, free take-back of inner ink bag/printhead, HP Planet Partners.<sup>4</sup>
- Choose from a wide range of compatible eco-conscious media.<sup>5</sup>
- HP Latex prints are recyclable, returnable, or non-hazardous and safe for disposal.<sup>6</sup>

For more information, please visit <http://www.hp.com/go/latex700series>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://hplatexknowledgecenter.com/>

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: <http://www.hp.com/go/learnaboutsupplies>

<sup>1</sup> Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

<sup>2</sup> HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.

<sup>3</sup> There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>4</sup> The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For ink bag and printhead take back, visit <http://www.hp.com/recycle> to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

<sup>5</sup> See <http://www.hp.com/go/mediasolutionslocator>.

<sup>6</sup> Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back program. Programs may not exist in your area. See <http://www.HPLFMedia.com/hp/ecosolutions> for details. HP large format printing materials, both unprinted and printed with Original HP Latex Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions.

## Technical specifications

### Print

|  |   |
|--|---|
| Printing modes                         | 105 m <sup>2</sup> /hr - Max Speed (1-pass)<br>31 m <sup>2</sup> /hr - High Speed (4-pass)<br>21 m <sup>2</sup> /hr - Production Fast (6-pass)<br>17 m <sup>2</sup> /hr - Production Quality, Textiles and Backlits (8-pass)<br>16 m <sup>2</sup> /hr - High Saturation (12-pass)<br>12 m <sup>2</sup> /hr - High Saturation Backlits and Textiles (14-pass) <sup>1</sup> |
| Print resolution                       | Up to 1200 x 1200 dpi   |
| Ink types                              | Water-based HP Latex Inks   |
| Ink cartridges                         | 8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Overcoat)  |
| Cartridge size                         | 1 L   |
| Printheads                             | 8 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Overcoat)   |
| Long-term print-to-print repeatability | 95% of colors ≤ 1.5 dE2000 <sup>2</sup>   |

### Media

|               |  |
|---------------|--|
| Handling      | Roll feed, take-up reel, wiper roller <sup>3</sup> , automatic horizontal cutter (for vinyl, banner and canvas <sup>4</sup> , paper-based media, and film) |
| Media types   | Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles <sup>5</sup>                                     |
| Roll size     | 254 to 1625-mm rolls (580 to 1625-mm rolls with full support)  |
| Roll weight   | 55 kg  |
| Roll diameter | 250 mm   |
| Thickness     | Up to 0.5 mm   |

### Applications

Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers

### Connectivity

|            |                               |
|------------|-------------------------------|
| Interfaces | Gigabit Ethernet (1000Base-T) |
|------------|-------------------------------|

### Dimensions (w x d x h)

|                |                       |
|----------------|-----------------------|
| Printer        | 2583 x 852 x 1402 mm  |
| Shipping       | 2800 x 1130 x 1270 mm |
| Operating area | 2793 x 2100 mm        |

### Weight

|          |        |
|----------|--------|
| Printer  | 261 kg |
| Shipping | 362 kg |

### What's in the box

HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, 2-in spindle adaptor

### Environmental ranges

|                       |                               |
|-----------------------|-------------------------------|
| Operating temperature | 15 to 30°C                    |
| Operating humidity    | 20 to 80% RH (non-condensing) |

### Acoustics

|                |  |
|----------------|--|
| Sound pressure | 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) |
| Sound power    | 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) |

### Power

|              |   |
|--------------|---|
| Consumption  | 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready)   |
| Requirements | input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord |

### Certification

|                 |   |
|-----------------|---|
| Safety          | IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)                          |
| Electromagnetic | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)                                 |
| Environmental   | ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Silver; OSHA; CE marking compliant; Meets AgBB criteria; French VOC A+; Greenguard Gold; UL Ecologo; ZDHC - Level 1 |

### Warranty

One-year limited hardware warranty

## Ordering information

### Product

|        |                      |
|--------|----------------------|
| YOU22A | HP Latex 700 Printer |
|--------|----------------------|

### Accessories

|        |  |
|--------|--|
| 21V10A | HP Latex 700/800 User Maintenance Kit    |
| 7HR16A | HP Latex 700/800 Textile Kit Accessory   |
| 7HR18A | HP Latex 700/800 Ink Collector Foams Kit |
| 7HR19A | HP Latex 700/800 Media Loading Accessory |
| T7U73A | HP Latex 500/700/800 Wiper Roller        |

### Original HP printing supplies

|        |  |
|--------|--|
| 4UU94A | HP 836 Optimizer Latex Printhead                 |
| 4UU96A | HP 836 Latex Maintenance Cartridge               |
| 4UV75A | HP 832 1-liter Black Latex Ink Cartridge         |
| 4UV76A | HP 832 1-liter Cyan Latex Ink Cartridge          |
| 4UV77A | HP 832 1-liter Magenta Latex Ink Cartridge       |
| 4UV78A | HP 832 1-liter Yellow Latex Ink Cartridge        |
| 4UV79A | HP 832 1-liter Light Cyan Latex Ink Cartridge    |
| 4UV80A | HP 832 1-liter Light Magenta Latex Ink Cartridge |
| 4UV81A | HP 832 1-liter Optimizer Latex Ink Cartridge     |
| 4UV82A | HP 832 1-liter Overcoat Latex Ink Cartridge      |
| 4UV95A | HP 836 Black/Cyan Latex Printhead                |
| 4UV96A | HP 836 Magenta/Yellow Latex Printhead            |
| 4UV97A | HP 836 Light Cyan/Light Magenta Latex Printhead  |
| 4UV98A | HP 836 Overcoat Latex Printhead                  |

### Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified<sup>6</sup>, FSC<sup>®</sup> certified<sup>7</sup>, meets AgBB criteria<sup>8</sup>)  
HP Photo-realistic Poster Paper  
HP Premium Satin Canvas  
HP Prime Matte Air GP (REACH compliant<sup>9</sup>)  
HP Premium Removable Gloss Adhesive Vinyl (REACH compliant<sup>9</sup>)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

### Service and Support

U13D9E HP 2 year Next Business Day with Defective Media Retention  
U13DFE HP 3 year Next Business Day with Defective Media Retention  
U13DKPE HP 1 year Post Warranty Next Business Day with Defective Media Retention  
U13DQPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

## ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard<sup>1</sup>
- Can win new business with odorless prints, UL ECOLOGO<sup>®</sup>/UL GREENGUARD Gold Certified ink, and more<sup>2</sup>
- Eco-Carton replaces plastic cartridge with 80% reduction in plastic, achieves 66% CO<sub>2</sub>e reduction<sup>3</sup>
- Zero landfill—local outer carton recycling, free take-back inner ink bag via HP Planet Partners<sup>4</sup>

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: <http://www.hp.com/ecosolutions>

<sup>1</sup> See <http://www.roadmaptozero.com>. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin.  
<sup>2</sup> There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see <http://www.ul.com/EL> and <http://www.ul.com/gg>.  
<sup>3</sup> CO<sub>2</sub>e reduction based on moving from plastic ink cartridge to cardboard HP Eco-Carton ink cartridge, with annual manufacturing savings of 291 tons and transport savings of 8 tons. Equivalent to 1,194,028 km (741,935 miles) driven by an average passenger vehicle or over 38 million smartphones charged.  
<sup>4</sup> The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/printhead/prints, visit <http://www.hp.com/recycle> to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction.

<sup>5</sup> Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.  
<sup>6</sup> The color variation between printed jobs has been measured at 12 pass mode on vinyl media following best practices for tiling layouts and within this limit: 95th percentile of pairwise color differences (95% of colors) ≤ 1 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 1 dE2000. Backlit substrates measured in transmission mode may yield different results.  
<sup>7</sup> Wiper roller is an optional accessory.  
<sup>8</sup> Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.  
<sup>9</sup> Textile Kit Accessory required for long runs of textile and porous textile.  
<sup>10</sup> UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>.  
<sup>11</sup> Trademark license code FSC-C115319.  
<sup>12</sup> With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See <http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building>.  
<sup>13</sup> This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](http://www.hp.com).



**AARQUEGROUP** FOR MORE INFORMATION CONTACT  
PARTNER OF CHOICE **AARQUE GROUP LIMITED**  
0508 22 77 83 [www.aarque.co.nz](http://www.aarque.co.nz)

