

Epson SureColor F9560/9560H

- Designed for custom fabric, soft signage and décor production
- Compact form factor with integrated media heater and ATU
- Enhanced productivity with easier management and reduced user intervention
- Choice of 4c and 6c models, the latter with a choice of LcLm for max gradation, OrVi for max gamut or FyFp for maximum brightness
- Epson Ultrachrome[™] dye sublimation ink ensures predictable performance with superior image quality and exceptional wash/UV durability
- Uses convenient 1.6 L ink pouches with a dual supply that supports hot-swap
- Oeko-Tex[™] compliant so garments can be worn by adults, children and infants¹
- Comprehensive single source warranty with onsite cover up to FIVE years²
- Supplied with Epson Edge Print PRO software and backed with advanced management and support via Epson Cloud Solution PORT

Epson SureColor Fabric F9560/9560H 4c & 6c 64" Dye Sublimation Printers

Product Specification	S
PRINTING TECHNOLOGY	
Printhead	2.64" MicroPiezo TFP® with Variable Sized Droplet Technology & Precision Dot Technology, ink-less nozzle status monitoring, auto compensation & self-cleaning, support optional user self-replacement ³
Print modes Nozzle configuration Maximum resolution	Uni & bi-directional 8 x 800 (F9560) / 12 x 800 (F9560H) 1200 x 600 dpi
INK SYSTEM Ink type Ink set	Epson Ultrachrome® DS DS/DS6 (extended) 4c F9560 HDkCYM 6c F9560H HDkCYM + LcLm or OrVi or FyFp
Storage PRINT PERFORMANCE ⁴	4 x 2 x 1.6 L (F9560) / 6 x 2 x 1.6 L (F9560H)
Max speed Standard production MEDIA SUPPORT	147 m²/hr 80 m²/hr fabric, 21m²/hr hard surface
Loading	Single roll, 250 mm max diameter with 2" or 3" core, $0.04 \sim 1.0$ mm thick, $300 \sim 1625$ mm width
Min print margins OPERATION	5 mm left/right, 5 mm top/bottom
Output	Roll-based with integrated heater and auto take-up (914 \sim 1625 mm wide)
Control panel Utility software	4.3" touchscreen with in-built help & QR-code support Epson Edge Dashboard with downloadable print profiles, Epson Cloud Solution PORT with costing and management tools
RIP software Interface Memory	Ships with Epson Edge Print PRO (Windows only) Ethernet (recommended) and USB 3.0 4 GB
ENVIRONMENTAL	15 2500 (15 2500 recommended)
Operational temp Operational humidity Power supply	15 ~ 35°C (15 ~ 25°C recommended) 20 ~ 80% (no condensation, 40 ~ 60% recommended) 240 V AC, 50 ~ 60 Hz, 3.2 W
Power consumption Operating noise	1040 W operating / 360 W ready / 3.2 W sleep 59 dB

PHYSICAL	
Dimensions (W x D x H)	2620 x 929 x 1020 mm
Weight	325 kg (F9560) / 327 kg (F9560H)
Shipping carton	3.0 x 1.2 x 1.1 m, 506 kg (printer only)
WHAT'S IN THE BOX⁵	
Printer, ink supply system, power cal	ble, reusable waste tank, maintenance kit, head
cleaning kit, dual HDkCYM ink set, 1	x roll Epson transfer media, utility software, RIP licens
& installation guide (online user guid	e).
CONFIGURATION OPTIONS	
SCF95601Y	4c printer with 1-yr warranty
SCF95603Y	4c printer with 1-yr warranty + 2-yr CoverPlus
SCF95605Y	4c printer with 1-yr warranty + 4-yr CoverPlus
SCF9560H1Y	6c printer with 1-yr warranty
SCF9560H3Y	6c printer with 1-yr warranty + 2-yr CoverPlus
SCF9560H5Y	6c printer with 1-yr warranty + 4-yr CoverPlus
CONSUMABLES	
C13S210103	Maintenance kit
C13T724000	Replacement 2 L waste tank
C13S210139	Head cleaning kit
C13T53L200/300/400/900	2 x 1.6 L C/Y/M/HDk ink pouches
C13T46D500/600	2 x 1.6 L Lc/Lm ink pouches
C13T46D700/800	2 x 1.6 L Fv/Fp ink pouches

1. The Epson dye sublimation ink used in the SureColor F9560 & F9560H printers when applied to polyester fabric, pass the requirements of the Oeko-Tex Standard 100 for human ecological requirements of Class I products for adults, children, and babies up to 36 months. The standard specifies testing criteria for the presence of harmful substances within a textile product and belongs to the International Association for Research and Testing in the field of Textile Ecology (Oeko-Tex).

2 x 1.6 L Or/Vi ink pouches

- 2 Warranty is provided for all non-consumable items associated with printers sourced through Epson Australia. Cover includes printheads. It can be extended through the purchase of optional CoverPlus, either separately or as part of a configuration package. Free onsite repair is provided in major metro locations. Service is conditional on a range of factors, including appropriate product usage, operation within the printer duty cycle, regular and appropriate user maintenance, use of correct and genuine Epson. CoverPlus requires activation, and connection to the Epson Cloud Solution PORT system. Visit www.epson.com.au/coverplus or www.epson.co.nz/coverplus for full details.
- 3 User self-replacement of the printhead requires activation of PORT.

C13T46DA00/D00


- 4 Performance figures presented are print speeds only. Actual production times will vary depending on computing platform, print application, file format, size and networking configuration.
- 5 Independent sourcing and use of a heat press is required. Ink and media is packaged separately. Additional Lc/Lm or Fy/Fp or Or/Vi ink must be ordered as required with the F9560H.



Pouch-based dual ink supply



User-replaceable printhead3



Epson Cloud Solution PORT



Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. Specifications are subject to change without notice. Visit www.epson.com.au or www.epson.co.nz for the latest information.



Epson Australia Pty Ltd Level 1, 3 Talavera Road Macquarie Park NSW 2113 Tel: 02 8899 3666 www.epson.com.au

Epson New Zealand
Level 2, 9 Fanshawe Street
Auckland 1010
Tel: 09 366 6855
www.epson.co.nz

07/2024

